

High Output Deluxe Basket Fan

J&D Manufacturing's Deluxe Basket Fan Series combines high output performance, low cost and energy efficiency to give you one of our best valued fan series available on the market today. The High Output Deluxe Basket Fan has a high velocity air pattern with quiet operation. All fans include a heavy duty hot dip galvanized mounting bracket.



Features

- Available in 24" , 30" and 36"
- Fan ships completely assembled
- Includes hot dip galvanized ceiling mount bracket
- 30" and 36" fans available in black (white on special order)
- Heavy gauge, corrosion resistant powder coated guards
- Single phase models include attached cord with 3-prong plug pre-wired for 115 Volts
- Guards meet OSHA 1910.212(1)(5) requirements
- Totally enclosed, maintenance-free, direct drive high-efficiency motors have completely sealed ball bearings and are covered by a **Two Years Warranty**
- Can be used with our misting/fogging product line

Part#	Size	HP	Volt	Amps	Hz	Phs	Spd	KW	RPM	Thrust CFM	Blade
VDB24	24"	1/2	115	4.8	60/50	1	S/Var^	.498	1,709	5,370	3- Alum
VDB303	30"	1/2	230/460	2.6/1.3	60/50	3	1	.527	827	6,840	3- Alum
VDB363	36"	1/2	230/460	4.8/2.4	60/50	3	1	.534	827	9,550	3-Galv

All units are DD (Direct Drive) and include the corresponding hot dip galvanized standard flag mount bracket with hardware.
 ~ These units come pre-wired for 115 Volts (electrician may rewire for 230 Volts)
 ^ Variable speed fans require separate variable speed control to adjust fan speed.
 Velocity measured center line at a distance 5 times the prop diameter.
Bold red text is data certified by BESS Labs using ANSI/AMCA Standard 230-12.